

Sub 036
A METHOD FOR GENERATING A DIVERSE SET OF TRAVEL OPTIONS

BACKGROUND

This invention relates to travel planning systems.

Computer travel planning systems such as airline
5 computer reservation systems used by airline reservation agents,
human travel agents, and automated travel agents such as internet
web sites , generally produce a relatively small set of
recommended travel options for a query that has a route and/or
time specification.

10 For air travel, usually the number of travel options
that a travel planning system produces is much smaller than the
total set that could possibly satisfy a traveller's request. For
example, a CRS may respond to a round-trip query specified by a
departure city and date and a return city and date with a set of
15 10 or so possible flight and fare combinations, even though there
may be thousands of combinations of flights that satisfy the
request.

20 In many cases, resource limitations prevent a travel
planning system from analyzing or generating more than a small
set of travel options. Moreover, for air travel it may be that
for each option the system needs to query airlines about seat
availability. The availability process places practical limits
the number of options that may be considered.

SUMMARY OF THE INVENTION

25 If a travel planning system is limited in the number of
options it can generate, it may be desirable that the travel
planning system consider or generate a diverse set of travel
options. The planning system can maximize its chance of
generating a good option by enforcing diversity in the set of
30 options generated.

The diversity process in the air travel planning system generates answers on several different airlines, thus the system is capable of satisfying a greater range of travellers.

Similarly, an air travel planning system that queries airlines about whether there are seats available on a limited number of flights may wish to choose flights at a diversity of flight times, in case flights at particular times of day are all full.

According to one aspect of the invention, travel planning system that outputs a set of travel options smaller than the complete set of travel options it has computed prunes the larger set of options to a smaller set with a diversity-based pruning process, where the larger set is represented by a compact representation.

One or more advantages are provided by the some of the aspects of the invention. The client process receives a set of pricing solutions provided in a compact representation. A preferred, compact representation of the set of pricing solutions is as a data structure comprising a plurality of nodes that can be logically manipulated using value functions to enumerate a set of pricing solutions. One preferred example is a graph data structure type particularly a directed acyclic graph that contains nodes that can be logically manipulated or combined to extract a plurality of pricing solutions. The client, can store and/or logically manipulate the set of pricing solutions to extract or display a subset of the set of pricing solutions without the need for additional intervention by the server.

BRIEF DESCRIPTION OF THE DRAWINGS

The foregoing features and other aspects of the invention will be described in further detail by the accompanying drawings, in which:

FIG. 1 is a block diagram of a client server travel

planning system.

FIG. 2 is a flow chart showing a server process used in the system of FIG. 1.

FIG. 3 is a flow chart showing a client process used in the system of FIG. 1.

FIGS. 3A-3B are diagrammatic representations of pricing graphs.

FIGS. 4A-4B are flow charts showing a faring process used in the server process of FIG. 2.

FIG. 5 is a flow chart showing the process for constructing a pricing graph.

FIG. 6 is a block diagram showing the relationship between the pricing graph and a graphical user interface for the travel planning system of FIG. 1.

FIG. 7 is a flow chart showing various enumeration functions.

FIG. 8 is flow chart of a diversity process for selecting a diverse set of travel options.

FIG. 9 is a flow chart depicting an example of a diversity process.

FIG. 9A is a flow chart depicting a process used with a pricing graph.

FIG. 10 is a flow chart of a process to generate a prioritized list of travel requirements for the diversity process of FIG. 3.

FIG. 11 is a flow chart of template process used in the diverstiy process.

FIG. 12 is a flow chart of an alternative diverstiy process to generate a diverse set of travel options from a larger set of travel options.

DETAILED DESCRIPTION

Referring now to FIG. 1, a travel planning system 10 is shown. The travel planning system can be used with various forms of travel such as airline, bus and railroad and is particularly adapted for air travel. It includes a server computer 12 having a computer memory or storage media 14 storing a server process 15. The server process includes a scheduler process 16 and a faring process 18. The scheduler process 16 is any suitable scheduler process that will produce from a travel request sets of flights that can satisfy the request. The faring process 18 is a process that determines a set of valid fares and links the set of valid fares to the sets of flights to form a pricing solution. The server process 15 can be configured to produce other travel-related information as a result of a user query. For example, the server process 12 can produce routes or airline suggestions, optimal travel times and suggestions for alternative requests.

The travel planning system 10 also includes a plurality of databases 20a, 20b which store industry-standard information pertaining to travel (e.g., airline, bus, railroad, etc.). For example, database 20a can store the Airline Tariff Publishing Company database of published airline fares and their associated rules, routings and other provisions, the so-called ATPCO database. Database 20b can be an inventory of current availability of airline information for a particular carrier and so forth. The databases 20a-20b are typically stored locally and updated periodically by accessing remote resources 21a, 21b that maintain the respective databases.

~~The system 10 also includes a plurality of clients 30a-30c implemented by terminals or preferably personal computers. The clients 30a-30c are coupled to the server 12 via a network 22 which is also used to couple the remote resources (21a-21c) that supply the databases 20a-20b to the server 12. The network 22 can be any local or wide area network or an arrangement such as~~

A1
Cont'd

~~the Internet.~~

Sub
#2

~~The clients 30a-30e are preferably smart clients. That is, using client 30c as an illustrative example, client 30c includes a client computer system 32 including a computer memory or storage media 34 that stores a client process 36 and a set of pricing solutions 38. The set of pricing solutions 38 in one embodiment is provided from the server process 16 and comprises a set of fares that are valid for a journey, and associated information linking the fares to the flight segments of the journey.~~

10

The set of pricing solutions 38 is obtained from the server 12 in response to a user request sent from the client 30c to the server 12. The server 12 executes the server process 15 using the scheduling process 16 and the faring process 18 to produce a set of pricing solutions for a particular journey. If requested by the client, for example client 30c, the server 12 will deliver the set of pricing solutions 38 to the requesting client 30c. Under control of the client process 36, the requesting client 30c can store and/or logically manipulate the set of pricing solutions 38 to extract or display a subset of the set of pricing solutions as a display representation 41 on the monitor 40.

15

20

SERVER PROCESS

Referring now to FIG. 2, the server process 18 is preferably executed on the server computer 12 but could be executed on the client computer 32. The server process 18 is responsive to a user input query 48. The user input query 48 would typically include minimal information needed to determine a set of pricing solutions. This information typically requires at a minimum, an origin and a destination for travel. In addition, the information could also include times, dates and so forth.

25


30

This query 48 is fed to the scheduler process 16 that produces a large number of itineraries, that is, sequences of flight segments between the origin and destination for each slice of a journey. Examples of scheduler systems that may be used include the OAG Flight Desk (Official Airlines Guide, a division of Reed Travel Group) or schedule components of computer reservation systems (CRS=s) such as Sabre7, Apollo7, Amadeus7 and WorldSpan7. It is preferable in order to obtain the largest number of possible itineraries to use a scheduler with dynamic connection generation. Such a scheduler is described in co-pending patent application entitled SCHEDULER SYSTEM FOR TRAVEL PLANNING SYSTEM, Serial No. 09/109,622, filed on July 2, 1998 y Carl G. deMarcken et al. and assigned to the assignee of the invention and incorporated herein by reference.

The scheduler process 16 provides the itineraries to a faring process 18. The faring process 18 provides a set of pricing solutions 38 by finding valid fares corresponding to the itineraries produced by the scheduler process 16. The faring process 18 validates the fares for inclusion in the set of pricing solutions 38. A preferred faring process that places fares and itineraries in a compact data structrure referred to herein in as a pricing graph is described in co-pending patent application entitled TRAVEL PLANNING SYSTEM, Serial No. 09/109,327 , filed on July 2, 1998 by Carl G. deMarcken et al. and assigned to the assignee of the invention and incorporated herein by reference.

The set of pricing solutions 38 is used by an availability system 58 that interrogates an airline inventory database 20b to determine whether there are seats available on particular flights for particular pricing solutions. The availability system 58 uses the airline inventory database 20b as a filter to remove from the set of pricing solutions 38 those

pricing solutions for which there are not available seats. The availability system 58 is shown after the faring process 18. However, it could be included at nearly any point in the server process 18. In addition, it is shown being fed by the pricing solution when it may only receive flight information from the scheduler process 16 depending on the airline.

sub A3  ~~The client system 30c receives the results from the server process 18. These results are the set of pricing solutions 38 and/or pricing solutions based upon availability. The client process 36 executed in the client 30c uses this information or a subset of it to access a booking system 62 to provide a booking and reservation for a user selected, enumerated pricing solution, as will be described below.~~

CLIENT PROCESS

Referring now to FIG. 3, the client process 36 receives a listing of possible itineraries from the scheduler process 16 as well as the set of fares from the faring process 18 or the availability system 58. The set of pricing solutions 38, if obtained from the faring process 18, will include a large number of pricing solutions for which there is not any available inventory. Therefore, the components would need to be first checked out with an airline prior to booking. The set of pricing solutions 38 if obtained after the availability system 58 should contain pricing solutions which have a high degree of availability for booking on an airline.

In one embodiment, the set of pricing solutions 38 is provided in a compact representation 38'. A preferred, compact representation 38' of the set of pricing solutions 38 is as a data structure comprising a plurality of nodes including itineraries and fares and that can be logically manipulated using value functions to enumerate a set of pricing solutions. One

preferred example is a graph data structure type particularly a directed acyclic graph (DAG) that contains nodes that can be logically manipulated or combined to extract a plurality of pricing solutions.

5 ~~The client process 36 receives the flight information~~
from scheduler process 16 and the pricing solution from the
faring process 18 or the availability system 56 and enumerates
pricing solutions from the directed acyclic graph (DAG)
representation. The enumerated set of pricing solutions is
10 rendered in a graphical user interface 41 on the client monitor
~~40 (FIG. 1) in a manner as will be described below.~~

~~In response to user input 76, the client 40 can~~
manipulate travel options and can query the local copy of the DAG
to produce and display a subset of pricing solutions enumerated
from the DAG that satisfy the query 76. The manipulation process
used to control the display and change the travel options will be
~~described below.~~

~~A directed acyclic graph (DAG) is used to represent the~~
compact set of pricing solutions 38' since, in general, the
number of nodes needed to represent a typical pricing solution
will be substantially less than the actual number of pricing
solutions represented by the DAG. This significantly increases
the efficiency of transfer of a set of pricing solutions 38 from
the server process 18 to the client process 36. The DAG
20 representation also minimizes the storage requirements for the
set of pricing solutions 38. The DAG representation permits the
use of powerful search, sorting and manipulation processes to
produce various subsets of set of pricing solutions in an
efficient manner. As used herein, a directed acyclic graph (DAG)
30 is a set of nodes connected by directed arcs, that have no loops
of arcs in the same direction. If a node A is connected to a
~~node B via an arc A6B, then A is called a parent of B, and B is~~

A6
Cont'd

~~called a child of A. Each node may have zero, one or many parents and zero, one or many children. As used herein, a pricing solution that is represented by a graph will be referred to as a pricing graph.~~

5 PRICING-GRAPH

A pricing graph that is produced by the faring process 18 and that represents a pricing solution includes three types of nodes. The first type of node is an exclusive node, i.e., "OR" node. An OR node N with children A, B and C represents an
10 exclusive choice between A, B and C. In other words, a pricing-solution involving node N contains either the fares and itineraries represented by A, or by B, or by C.

The second type of node is a collection node, i.e., an "AND" node. An AND node N with children A, B and C represents
15 the sum of A, B and C. In other words, a pricing solution involving N contains all the fares and itineraries found within A, B and C.

The third type of node is a terminal node. Terminal nodes are used to hold pricing objects. Pricing objects include
20 fares, itineraries, surcharges, routes, prices, booking codes, taxes, rules/restrictions and other information of the user or information that might be part of a travel option. Collectively, "AND" and "OR" nodes are non-terminal nodes.

An example of the pricing-graph for a hypothetical
25 round-trip journey is presented below in TABLE 1. For each node, its type and children are listed. If a node is a terminal, the fare or itinerary is provided. Many nodes in the pricing graph have more than one parent.

TABLE 1

Node	Type	Children	Object
0	OR	Nodes 1, 2, 3	
1	AND	Nodes 10, 14, 17, 17	

2	AND	Nodes 4, 5	
3	AND	Nodes 13, 15, 19, 19	
4	OR	Nodes 8, 9	
5	OR	Nodes 6, 7	
6	AND	Nodes 14, 16	
7	AND	Nodes 15, 18	
8	AND	Nodes 13, 16	
9	AND	Nodes 13, 18	
10	OR	Nodes 11, 12	
11	Itin.		Slice 1: BOS6LAX UA023
12	Itin.		Slice 1: BOS6DFW UA100, DFW6LAX UA103
13	Itin.		Slice 1: BOS6SAN NW222
14	Itin.		Slice 2: LAX6BOS UA515
15	Itin.		Slice 2: SAN6BOS NW223
16	Fare		UA BOS-LAX One-way AY
17	Fare		UA BOS-LAX Round-trip AQE7NR
18	Fare		NW BOS-SAN One-way AF
19	Fare		NW BOS-SAN Round-trip AH7NR

This pricing-graph represents a total of nine pricing solutions. These solutions can be extracted from the pricing-graph by descending from the root node, node 0. At every OR node a choice between children is made, and the choice determines the pricing-solution that results. At every AND node each child branch is descended, and the results are combined.

The term BOS6LAX UA023 is an itinerary which uses standard nomenclature to represent airports BOS and LAX, airline UA, and flight number 023. In general, conventional nomenclature used in the airline industry will be used herein.

~~The set of pricing-solutions that represented in the pricing-graph is presented in TABLE 2 below.~~

TABLE 2

Solution Number	Itineraries	Fares
1	Slice 1: BOS6LAX UA023 Slice 2: LAX6BOS UA515	UA BOS-LAX RT AQE7NR UA BOS-LAX RT AQE7NR
2	Slice 1: BOS6LAX UA023 Slice 2: LAX6BOS UA515	UA BOS-LAX OW AY UA BOS-LAX OW AY
3	Slice 1: BOS6LAX UA023 Slice 2: SAN6BOS NW223	UA BOS-LAX OW AY NW BOS-SAN OW AF

4	Slice 1: BOS6DFW UA100, DFW_LAX UA103 Slice 2: LAX6BOS UA515	UA BOS-LAX RT AQE7NR UA BOS-LAX RT AQE7NR
5	Slice 1: BOS6DFW UA100, DFW_LAX UA103 Slice 2: LAX6BOS UA515	UA BOS-LAX OW AY UA BOS-LAX OW AY
6	Slice 1: BOS6DFW UA100, DFW_LAX UA103 Slice 2: SAN6BOS NW223	UA BOS-LAX OW AY NW BOS-SAN OW AF
7	Slice 1: BOS6SAN NW222 Slice 2: LAX6BOS UA515	NW BOS-SAN OW AF UA BOS-LAX OW AY
8	Slice 1: BOS6SAN NW222 Slice 2: SAN6BOS NW223	NW BOS-SAN RT AH7NR NW BOS-SAN RT AH7NR
9	Slice 1: BOS6SAN NW222 Slice 2: SAN6BOS NW223	NW BOS-SAN OW AF NW BOS-SAN OW AF

The pricing-graph encodes the requirement that two itineraries are combined, one from slice 1 and one from slice 2, to form a pricing solution. Further, each itinerary is spanned by fares. In this case each pricing solution involves two fares, and round-trip fares are combined with like round-trip fares. In most circumstances, the number of nodes in the pricing-graph is small compared to the number of pricing-solutions those nodes represent. In many cases, a graph of 10,000 or so nodes can represent more than 1,000,000,000 pricing-solutions.

Referring now to FIG. 3A, the nodes of the pricing graph corresponding to Table 1 are shown, as an example. This figure illustrates the manner in which nodes in the pricing graph data structure as represented in Table 1 are combined to provide the pricing solutions shown in Table 2. Using pricing solution No. 1 (from TABLE 2) as an example, it can be shown that starting at the top of the graph at node 0, node 0 allows for a choice between nodes 1, 2, and 3. For pricing solution No. 1, Node 1 is chosen. Node 1 is the AND node that points to nodes 10 and 14, and has two pointers to node 17. Node 10 is an OR node which provides a choice of either nodes 11 or nodes 12. Node 11 as shown in FIG. 3A corresponds to a terminal node, the itinerary (>BOS-LAX UA 023). Node 12 corresponds to a terminal node, the itinerary BOS-DFN UA 100, DFN-LAX UA 103. This second choice in node 10 will provide pricing solutions corresponding to numbers

4-6, respectively. Therefore, selecting node 11 provides the itinerary for the first slice of solution 1. The fare for pricing solution 1 is provided by node 17 which has two pointers, one for each slice, to the fare "US BOS-LAX RT QE7NR"

5 corresponding to the fare shown for pricing solution no. 1 in Table 2 for the first slice. The second itinerary for pricing solution no. 1 is provided by node 14 which is referenced in AND node 1 that points to the itinerary LAX-BOS UA 515. The corresponding fare is also from terminal node 17 since it is a
10 round trip fare UA BOS-LAX RT QE7NR.

A second one of the pricing solutions, for example, the pricing solution 4 incorporating the terminal node 12 is provided by starting at node 0, and using node 1. Node 1 is an AND node requiring that nodes 17 (twice), node 10, and node 14 be
15 included. Node 10 is an OR node as mentioned above and is used to select node 12 which is the itinerary including segments ABOS6DFW UA 100" and ADFW6LAX UA 103". From node 1, node 14 the return itinerary LAX-BOS UA 515 also is reached. Node 17 also is chosen which contain the round trip fares. Similarly, the
20 remaining ones of the pricing solutions can be extracted from the pricing graph in the same manner as the two examples given above.

As mentioned above, a graph will typically have many more pricing solutions than nodes in the graph. The example just illustrated in conjunction with FIG. 3A has 9 pricing solutions
25 and 19 nodes which is an exception to that general rule. Another example of a pricing graph which does satisfy that general observation is shown in conjunction with FIG. 3B.

Referring now to FIG. 3B, a pricing graph is shown having 43 nodes N0-N42 that when combined represent 856 pricing
30 solutions. Each node in the pricing graph has a number associated with it corresponding to the number of pricing solutions that it represents. In order to make this illustration

of manageable size, identifiers (representing the nodes of the terminals) are substituted in the pricing graph for the actual terminal objects of the graph. Thus, as shown in FIG. 3B, outbound and return itineraries, and fare nodes are represented by the Nodes N20-N42.

This pricing graph (TABLE 3) has 9 itineraries which can be combined with 14 fares represented by 13 AND nodes and 7 OR nodes. The pricing objects are represented by 23 nodes. The pricing graph has a combined total of 43 nodes to represent 876 pricing solutions.

FIG. 3B shows examples of a pricing graph for a round trip LAX-BOS journey. This example shown in FIG. 3B is generally more representative of an outcome of a faring search. That is, generally the pricing graph represents more pricing solutions than nodes contained in the graph.

TABLE 3

Node	Type	Children	Object
0	AND	Nodes 1, 6, 11	
1	OR	Nodes 2, 3, 4	
2	AND	Nodes 5, 40	
3	AND	Nodes 41, 41	
4	AND	Nodes 42, 42	
5	OR	Nodes 39, 40	
6	OR	Nodes 7, 8, 9	
7	AND	Nodes 20, 10	
8	AND	Nodes 21, 10	
9	AND	Nodes 22, 10	
10	OR	Nodes 23, 24, 25, 26	
11	OR	Nodes 12, 13, 14, 16, 17, 18	
12	AND	Nodes 27, 15	
13	AND	Nodes 28, 15	
14	AND	Nodes 29, 15	
15	AND	Nodes 30, 31, 32	
16	AND	Nodes 33, 19	
17	AND	Nodes 34, 19	
18	AND	Nodes 35, 19	
19	OR	Nodes 36, 37, 38	
20	Itin.		Slice 1: LAX6DFW NW100, DFW6BOS AA223
21	Itin.		Slice 1: LAX6DFW NW137, DFW6BOS AA223
22	Itin.		Slice 1: LAX6DFW NW137, DFW6BOS AA414

23	Fare		DFW, LAX NW AY OW
24	Fare		DFW, LAX NW AF OW
25	Fare		DFW, LAX NW AC OW
26	Fare		DFW, LAX NW AQA7" OW
27	Itin.		Slice 2: BOS6DFW AA67, DFW6LAX CO716
28	Itin.		Slice 2: BOS6DFW AA67, DFW6LAX CO717
29	Itin.		Slice 2: BOS6DFW AA67, DFW6LAX CO719
30	Fare		DFW, LAX CO AF OW
31	Fare		DFW, LAX CO AC OW
32	Fare		DFW, LAX CO AY OW
33	Itin.		Slice 2: BOS6DFW AA852, DFW6LAX DL186
34	Itin.		Slice 2: BOS6DFW AA852, DFW6LAX DL180
35	Itin.		Slice 2: BOS6DFW AA852, DFW6LAX DL343
36	Fare		DFW, LAX DL AF OW
37	Fare		DFW, LAX DL AC OW
38	Fare		DFW, LAX DL AY OW
39	Fare		DFW, BOS AA AQE7NR RT
40	Fare		DFW, BOS AA AQE7IP RT
41	Fare		DFW, BOS AA AQE14NR RT
42	Fare		DFW, BOS AA AQE21NR RT

THE FARING SYSTEM

Referring now to FIGS. 4A and 4B, the faring process 18 includes a process 80 to retrieve itinerary sets for all slices in an itinerary. The itinerary sets are provided from the scheduler process 16 for each slice of a journey where a slice corresponds to a direction of travel. Thus, for example, for a round trip journey there would be two slices, one for the outbound part of the journey and one for the return part of the journey. The faring process 18 decomposes 82 the itinerary into faring atoms. As used herein, faring atoms refer to a sequence of flight segments or equivalently legs that are spanned by a single fare. For example, the itinerary

UA005 from DFW to BOS at 12:30 on 12NOV

UA010 from BOS to YYZ at 18:00 on 12NOV

AC121 from YYZ to YVR at 01:00 on 13NOV

permits the following faring-atoms as shown in TABLE 4.

TABLE 4

Faring-Atom Number	Legs and Departure Times
1	DFW6BOS UA005 12NOV 12:30
2	BOS6YYZ UA010 12NOV 18:00
3	DFW6BOS UA005 12NOV 12:30 BOS6YYZ UA010 12NOV 18:00
4	YYZ6YVR AC121 13NOV 01:00

A faring atom is represented by a data structure that preferably includes the following fields as shown in TABLE 5:

TABLE 5

Faring-Atom fields	Use
legs-and-departure-times	A list of legs and their departure times and dates.
faring-market	The faring-market that this faring-atom is in.
cached-results	A storage space used to eliminate redundant computation in the rule-checking process. As rule record-2s are applied to faring-atoms, the results are stored in this field. If the same record-2 is applied again, the answer is retrieved rather than recomputed.
priceable-unit-labels	A list of the priceable-unit-labels that the faring-atom enters into.

After the faring process 18 decomposes the itineraries into faring atoms, the faring process 18 retrieves fares 84 and rules 86 for each faring atom by accessing the fares/rules database 20a mentioned above. At this point a fare=s routing is retrieved from a routing database and applied to a faring atom. If the routing test fails, the fare cannot be applied to the faring atom and a fare component is not built.

The faring process 18 applies the rules 88 to the faring atoms to produce fare components. Fare-components are combinations of faring-atoms and fares. Fare-components (TABLE 6) are produced if a fare=s rules pass a preliminary check on a faring-atom. They are used to store deferred rules (e.g., deferred record-2s and combinability record-2s) that are applied at a later stage of processing. Fare components also store extra information produced during the rule-checking process, such as information about surcharges and penalties and discounts that are

A9 Cont'd
~~applied to the base fare price.~~

TABLE 6

Sub A31

Fare-Component fields	Use
fare	The fare-component=s fare.
faring-atom	The fare-component=s faring-atom.
deferred-record-2s	A list of non-category-10 record-2s that have not been fully evaluated.
combinability-record-2	If the fare=s rules include a category-10 (AFare Combinability record-2, it is stored here.
surcharges	A list of surcharges, penalties, discounts and other pieces of information produced during the rule-checking process.

10 ~~From the fare components the faring process 18 constructs 90~~
priceable units. For certain types of rules such as those which
require access to fares and/or flights from outside of the fare
component, those rules are stored in the fare component for later
or deferred evaluation. The priceable unit process 90, takes
valid fare components and constructs priceable units from the
fare components. This process 90 involves grouping fare
components from different slices and checking fare component
combination restrictions. At this stage of processing, the rules
~~deferred in step 88 are reapplied.~~

Sub A10

20 Priceable units are represented by priceable-unit-cores and
priceable-unit-labels. Priceable-unit-cores are collections of
fares and other information associated with fares within a
priceable-unit, such as discounts and penalties and surcharges.
Priceable-unit-cores (TABLE 7) are referenced by priceable-unit-
25 labels.

TABLE 7

30

Priceable-Unit-Core fields	Use
fares	A list of fares.
slice-numbers	A list of the slices the fares originate from.

surcharges	A list of surcharges, penalties, discounts and other pieces of information produced during the rule-checking process.
------------	---

Priceable-unit-labels group a set of priceable-unit-cores with sets of faring-atoms. Together, they are used to represent sets of priceable-units (TABLE 8).

TABLE 8

Priceable-Unit-Label fields	Use
priceable-unit-cores	A set of priceable-unit cores.
slice-numbers	A list of the slices the fares and faring-atoms originate from.
faring-atom-sets	A list of sets of faring-atoms, one per slice.

When all the fare components within a priceable unit are known, rules that were deferred from the processing 88 are applied 92 to the priceable unit sets of faring atoms.

~~After evaluation of the deferred record 2s at the priceable unit stage, the itineraries and priceable units are grouped together into complete set of pricing solutions. This occurs by a link process 94 that links itineraries to corresponding pricing units from different slices to provide the pricing solution. At this juncture, any remaining cross priceable unit fare combinability checks are performed to eliminate invalid combinations.~~

The linking process involves two additional data structures slice-label-sets and open-label-sets. Slice-label-sets group itinerary divisions by the multi-slice priceable-unit-labels they can enter into. In each slice of a journey, a unique slice-label-set is constructed for every set of multi-slice priceable-unit-labels. Each slice-label-set stores both the set of multi-slice priceable-unit-labels and a set of *itinerary-label-holders*, which contain single-slice priceable-unit-labels on a per-itinerary basis. Each slice-label-set is a pair of an itinerary

and a set of *division-label-holders*. Each of these division-label-holders is a pair of a division and a set of sets of single-slice priceable-unit-labels (TABLE 9).

TABLE 9

5	Slice-Label-Set fields		Use
	multi-slice-PU-labels		A set of multi-slice PU-labels.
	itinerary-label-holders		A set of itinerary-label-holders.
10	Itinerary-Label-Holder fields		Use
	itinerary		An itinerary.
	division-label-holders		A set of division-label-holders.
	Division-Label-Holder fields		Use
	division		An itinerary division.
	single-slice-PU-label-sets		A set of sets of single-slice PU-labels.

Open-label-sets (TABLE 10) are used to summarize the state of the linking process 94. Each is a set of "open" multi-slice priceable-unit-labels and a set of *backward-links*. Each of these backward-links is a pair of a slice-label-set and an open-label-set.

TABLE 10

20	Open-Label-Set fields		Use
	open-PU-labels		A set of open multi-slice PU-labels.
	backward-links		A set of backward-links.
25	Backward-Link fields		Use
	slice-label-set		A slice-label-set.
	open-label-set		An open-label-set.

~~The pricing solution resulting from the linking process 94 is used to construct a pricing graph from the various data structures built during the preceding processes. This pricing graph is transmitted to the client process or can be stored for later use or transmission. A pseudocode representation of the high level processing logic involved in the above search procedure is set out below in TABLE 11.~~

Sub
30
A12

TABLE 11

```

price-itinerary-sets(itinerary-sets, fare-database, rule-database, routing-database, environmental-information)
//
// itinerary-sets is a set of sets of itineraries, one per slice.
// environmental-information contains information about the passenger, the current date, the location
// where tickets will be purchased, and other non-itinerary-based information that is necessary for applying
// fare rules.
//
Let faring-market-sets = {}

// Construct itinerary-divisions, faring-markets and faring-atoms.
Let slice-number = 1
For itinerary-set in itinerary-sets
//
// create-divisions constructs the itinerary-divisions, faring-markets and faring-atoms for
// all the itineraries within a slice. It returns a set of faring-markets.
faring-market-sets += create-divisions(itinerary-set, slice-number, fare-database)
slice-number += 1

// Apply fare rules, constructing fare-components in each faring-market.
For faring-market-set in faring-market-sets
//
// apply-fare-rules constructs fare-components for each faring-market within a slice.
// This process contains pseudo-code for apply-fare-rules.
apply-fare-rules(faring-market-set, fare-database, rule-database,
routing-database, environmental-information)

// Create priceable-units.
// for create-priceable-units
create-priceable-units(faring-market-sets)

// Link itineraries between slices. This procedure returns either nil, if there are no pricing-solutions, or
// a root open-label-set. This process is described in link-itineraries
Let root-object = link-itineraries(itinerary-sets)
If (root-object = nil)
return(nil)

// Create the pricing-graph from the data-structures that have been built in the preceding steps.
// This process includes pseudo-code for create-pricing-graph.
Let root-node = create-pricing-graph(root-object)

// Return the pricing graph.
return(root-node)

```

PRICING GRAPH

⁵ ~~Referring now to FIG. 5, a pricing graph 38' (FIG. 3) is produced containing logically combinable nodes that can be used~~

SUB
A13

to efficiently and compactly represent a set of pricing solutions 38 (FIG. 1). The pricing graph 38' as used herein is a so-called directed acyclic graph although other types of representations could be used. For example, a grammar could be used.

The pricing graph 38' is constructed 300 from data structures 302 (summarized below in TABLE 12 and mentioned in conjunction with FIGS. 4A-4B) provided during the preceding processes. The data structures convert 304 to one or more nodes in the pricing graph. The open-label-set data structure becomes an OR node and its children are the converted versions of its backward links. Each backward link in the open label set is converted to an AND node. If a pricing object is shared, for example, a priceable unit core is shared between several priceable unit labels, then its counterpart nodes in the pricing graph will be shared so that the size of the pricing graph is not unnecessarily enlarged. The converted nodes are placed 306 in the pricing graph nodes. Terminal objects such as fares and itineraries undergo essentially no conversion. They are placed 308 into special terminal nodes with no children and are obtained from the various data structures that have the pricing objects.

TABLE 12

Data-Structure Type	Type	Child Fields
open-label-set	OR	<i>backward-links</i> (each a backward-link).
backward-link	AND	<i>open-label-set</i> (an open-label-set). <i>slice-label-set</i> (a slice-label-set).
slice-label-set	AND (OR)	<i>multi-slice-PU-labels</i> (each a priceable-unit-label). <i>itinerary-label-holders</i> (each an itinerary-label-holder). The itinerary-label-holders are put into an OR and the OR is placed under the AND, which also includes all multi-slice-PU-labels.
itinerary-label-holder	AND (OR)	<i>itinerary</i> (an itinerary). <i>division-label-holders</i> (each a division-label-holder). The division-label-holders are put into an OR and the OR is placed in an AND with the itinerary.

division-label-holder	OR (AND)	<i>single-slice-PU-label-sets</i> (each a set of sets of PU-labels). The inner sets are put into ANDs, and these are all embedded under an OR.
priceable-unit-label	OR	<i>priceable-unit-cores</i> (each a priceable-unit-core).
priceable-unit-core	AND	<i>fares</i> (each a fare). <i>surcharges</i> (each a surcharge, penalty, discount, etc.)
fares	Term	
itinerary	Term	
surcharge	Term	

In cases where a node has only one child, there is no need to produce the node. Rather, a direct link can be passed to its child. This does not alter the interpretation of the pricing-graph, but can result in a smaller graph.

The pseudo-code below TABLE 13 summarizes construction of the pricing graph, given the "root" open-label-set that is the output of the linking process.

TABLE 13

create-pricing-graph(root-object)

Let nodes = {}

Subroutine convert-object(object)

// Convert the object and cache the result, so that nodes with multiple parents are shared

Let node = find(object, nodes)

If (node = nil)

node = convert(object)

nodes += node

return(node)

Subroutine convert-objects (objects)

// Convert the set of objects and return a set of nodes.

Let result = {}

For object in objects

result += convert-object(object)

return(result)

Subroutine create-node(children, type)

// Create a node of type type with children children, if there is more than one child.

// Otherwise the node is unnecessary, and the only child is returned.

If (length(children) = 1)

return(first(child))

Else

Let node = new-node()

node.type = type

node.children = children

node.terminal-object = nil

return(node)

```

Subroutine convert(object)
  Let object-type = type(object)

  If (type = open-label-set)
    return(create-node(convert-objects(object.backward-links), OR))
  Else If (type = backward-link)
    return(create-node(list(convert-object(object.slice-label-set), convert-object(object.open-label-set)), AND))
  Else If (type = slice-label-set)
    Let children = convert-objects(object.multi-slice-PU-labels)
    children += create-node(convert-objects(object.itinerary-label-holders), OR)
    return(create-node(children, AND))
  Else If (type = itinerary-label-holder)
    Let children = convert-objects(object.division-label-holders)
    children += create-node(convert-objects(object.itinerary), OR)
    return(create-node(children, AND))
  Else If (type = division-label-holder)
    Let children = {}
    For single-slice-PU-label-set in object.single-slice-PU-label-sets
      children += create-node(convert-objects(single-slice-PU-label-set), AND)
    return(create-node(children, OR))
  Else If (type = priceable-unit-label)
    return(create-node(convert-objects(object.priceable-unit-cores), OR))
  Else If (type = priceable-unit-core)
    return(create-node(append(convert-objects(object.fares), convert-objects(object.surcharges)), AND))
  Else // object is a terminal.
    Let node = new-node()
    node.type = terminal
    node.children = {}
    node.terminal-object = object
    return(node)

return(convert-object(root-object))

```

TABLE 13 (cont.)

~~The pricing graph 38' resulting from the search procedure 54~~
 provides a compact way for representing a very large number of
 set of pricing solutions. By the above process, it is often
 possible to obtain a very large number of pricing solution
 components. Although the number of pricing solutions can be
 returned in the form of a simple list, this is not desirable. A
 very large number of pricing solutions can be difficult to
 manipulate, enumerate and interrogate and to transfer/transmit
 across a network since the amount of data involved is very large.
 The pricing graph 38' provides a more compact way of representing
 these pricing solutions. ~~The compact representation of the~~

range of set of pricing solutions is generated where choices are represented explicitly and redundancy is removed wherever possible.

5 *Sub A38*
~~As mentioned above, the pricing graph 38' produced by the search procedure 54 includes three types of nodes. The first type of node is a node that represents choices called "LOGICAL OR" nodes. The second type of node is a node that represents collections referred to as "LOGICAL AND" nodes. A third type of node represented in the pricing graph is a terminal node that represents pricing objects.~~

10
15
A data structure representation (TABLE 14) of the nodes is set out below. Each node contains a "type", which specifies whether the node is an AND node, an OR node or a terminal node. The data structure also contains either list of children (if the node is an AND node or an OR node) or a terminal object (if the node is a terminal). The node contains fields that store values used by algorithms that manipulate the pricing graph 38'.

TABLE 14

20 *Sub A38*

Node fields	Use
type	Either AND, OR or TERMINAL
children	A list of child-nodes, if node is AND or OR.
terminal-object	A terminal-object such as a fare or itinerary, if the node is TERMINAL.
active?	True or false, depending on whether the node is active.
inner-value	The node=s minimum possible inner-value.
outer-value	The node=s minimum possible outer-value.
total-value	The node=s minimum possible total-value.
best-child	For OR-nodes, the child with the least-positive inner-value.

25

30
As mentioned above, the pricing graph 38' is a compact representation of a set of set of pricing solutions. The typical number of set of pricing solutions represented by pricing graph ranges from tens of millions into hundreds of billions with the

number of nodes in the graph ranging from thousands to tens of thousands. The pricing graph can be easily stored and/or transmitted over a network or other connection to a client and represents complete representation of all or substantially all of possible pricing solutions. Therefore, the pricing graph 38' can be used by a smart client without further intervention from the server 12.

MANIPULATING THE PRICING-GRAPH

~~Referring now to FIG. 6, a high-level illustration of a process 300 that operates on the pricing graph 38' typically as a client process 36 on the client computer system is shown. The process 300 includes a user query 302 that passes parameters into a process 304 and a value function 306 to extract from the pricing graph 38' certain pricing solutions 308 that satisfy parameters specified by the user query 302. The extracted pricing solutions are returned as a list 308 or other representation. Generally the pricing solutions are displayed on the display 40. Display software 309 handles production of GUI=~~
~~41 to present the information.~~

~~The pricing solution list 308 will contain pricing solutions extracted from the pricing graph 38' in accordance with user specified parameters from the user query 302 using one of the processes 304 and one of 7, illustrative processes are shown. In particular, in response to the user query 302, one of the processes is executed. The processes 304 can comprise a find best "value" and pricing solutions associated with the value (e.g., price) process 304a; find best "value" and pricing solutions associated with the value for "node" (e.g., find best price for a particular itinerary) process 304b; an enumeration for "N" pricing solutions 304c; or an enumeration process that lists the pricing solutions according to some "value."~~

Additional enumeration processes can be provided to produce query results corresponding to different ways of looking at pricing solutions extracted from the pricing graph 38'. A node invalidating process 304e that invalidates selected nodes from contributing to a pricing solution is also included.

Examples of each of these processes are set forth below.

Efficient algorithms 304 are used for manipulating this representation to extract information of interest and to enumerate set of pricing solutions from the structure. For example, it is possible to quickly extract the cheapest solution; to find the cheapest solution involving selected fares and itineraries; to verify whether any pricing solution remains if specific fares or itineraries are excluded; to enumerate solutions under various orderings and so forth. Furthermore, the representation is compact enough so that it can be efficiently stored and transmitted such as from the server to the client. One benefit, therefore, is that after a single fare search 54 in the server process 16, the server process 16 transfers the pricing graph 38 to the client process 36. The client process 36 can examine and manipulate the large space of pricing solutions represented in the pricing graph 38' without further interaction with the server process 18.

For the set of pricing solutions represented by the pricing graph 38' to be useful, processes are provided to extract pricing solutions from the graph and manipulate the set of pricing solutions, as depicted in FIG. 7. In general, each of the enumeration processes to be described operate on the pricing graph to extract pricing solutions from the pricing graph according to particular criteria that can be set, for example, by a client system 30c (FIG. 2) in response to a user query 48 (FIG. 4). Examples of user queries as well as a display representation for information extracted from the pricing graph will be

A20
Cont'd

~~described below.~~

5 An example of an enumeration function enumerates pricing solutions in a specific order. For example, an enumeration function can enumerate the 100 cheapest pricing solutions represented by the pricing graph 38'. A second enumeration function can find extreme points of the set of pricing solutions. This can be used, for example, to find the most convenient pricing solution. In addition, a value function can specify a minimum value of some value over the set of pricing solutions

10 that involve a particular node. One value function finds for each itinerary the cheapest pricing solution that involves that itinerary or the shortest total duration of any pricing solution that involves that itinerary.

15 In addition, each of the above operations can be performed on a subset of the graph. For example, it may be desirable to enumerate the 100 cheapest solutions that involve a given itinerary or finding the most convenient solution that involves only refundable fares or includes only certain airlines or excludes certain airlines.

20 **VALUE FUNCTIONS**

~~There are many processes or operations on the pricing graph 38' use a value-function, a function that operates on the terminal nodes of the pricing graph 38' and returns a numerical value that can be used to rank pricing-solutions. Examples of value-functions include price computed by summing the prices of fares (and penalties and surcharges) in a pricing-solution, duration, or convenience (that might be a mix of total travel-time with penalties for stops and airline-changes, for example), or mixes of each.~~

30 Many of the processes used to manipulate the pricing graph 38' depend on a value-function being decomposable into the sum of

a second function that is applied to individual terminal nodes in the pricing-graph. The "price value function" meets this requirement, because the total price of a pricing-solution is equal to the sum of the prices of fares. Many expressions of convenience also meet this requirement, including those that can be computed as the sum of a function applied to individual itineraries. However, there are some value-functions that cannot be placed into this form. An example is a "convenience" function that checks whether travel in different slices is on the same airline. Such a function depends on all itineraries at once.

In general, in the discussion below, the term node-value-function is used to refer to a function that is applied to individual nodes in the pricing-graph, and summed to produce the value of an entire itinerary. The term value-function is used for the more general case of a function that may or may not be decomposable into the sum of a node-value-function applied to each terminal in the pricing-graph.

FINDING THE BEST PRICING SOLUTION

The first process 304a is an example of one that finds extreme points of the set of pricing-solutions, such as the cheapest pricing-solution.

Assuming that it is desired to find a pricing-solution that minimizes some value-function that can be decomposed into a node-value-function F , the best pricing solution could be found by enumerating all pricing-solutions and applying F to each of them. This is impractical because of the large number of set of pricing solutions.

The Best Price algorithm 304a efficiently finds the cheapest (best) price by starting at the "bottom" of the pricing-graph and constructing the best solution for each node by looking at the best solution of its children. In this way it works in one

pass from the bottom of the graph to the top. At the end of the process the root node contains the best pricing solution for the entire pricing graph 38.

The algorithm proceeds as follows: first, the nodes in the graph are ordered by depth and placed in a list, so that
5 iterating over the list ensures that a child node is always encountered before its parent(s). Then, iterating across the list, the best value of F is computed for each node, using the already-computed values of F for its children. At this point
10 every node in the graph is marked with its inner-value. The inner-value of a node is the best possible value of the function F on the set of (partial) pricing-solutions represented by the node. As inner-values are computed, for every OR node the child with the lowest inner-value is computed and stored. Finally, the
15 best pricing solution can be constructed by starting at the root of the graph and collecting children. Whenever an OR node is encountered, the best child is chosen (the child with the lowest inner-value).

If a node is a terminal fare or itinerary, then its inner-value is the value of F applied to the node. If the node is an
20 AND, representing a combination, then the minimum value of F over the partial solutions it represents is the sum of the minimum values of F over the partial solutions represented by each of its children. If a node is an OR, representing a choice, then the
25 minimum value of F over the partial solutions it represents is found by making the optimal choice of children, that is, the child with the minimum inner-value. So the inner-value of an OR is the minimum of the inner-values of its children.

The pseudo-code in TABLE 15 summarizes the computation of
30 inner-values. The function sort-nodes takes a root node and returns a list of all nodes under it, sorted by depth with the root node at the end. The procedure compute-inner-values takes

in a sorted list of nodes as would be produced by sort-nodes, and a node-value-function. The procedure find-optimal-solution takes in a root-node and a node-value-function, calls sort-nodes and compute-inner-values to calculate inner-values for all nodes in the pricing-graph, and constructs a pricing-solution.

5

4100
4101
4102
4103
4104
4105
4106
4107
4108
4109
4110
4111
4112
4113
4114
4115
4116
4117
4118
4119
4120
4121
4122
4123
4124
4125
4126
4127
4128
4129
4130
4131
4132
4133
4134
4135
4136
4137
4138
4139
4140
4141
4142
4143
4144
4145
4146
4147
4148
4149
4150
4151
4152
4153
4154
4155
4156
4157
4158
4159
4160
4161
4162
4163
4164
4165
4166
4167
4168
4169
4170
4171
4172
4173
4174
4175
4176
4177
4178
4179
4180
4181
4182
4183
4184
4185
4186
4187
4188
4189
4190
4191
4192
4193
4194
4195
4196
4197
4198
4199
4200
4201
4202
4203
4204
4205
4206
4207
4208
4209
4210
4211
4212
4213
4214
4215
4216
4217
4218
4219
4220
4221
4222
4223
4224
4225
4226
4227
4228
4229
4230
4231
4232
4233
4234
4235
4236
4237
4238
4239
4240
4241
4242
4243
4244
4245
4246
4247
4248
4249
4250
4251
4252
4253
4254
4255
4256
4257
4258
4259
4260
4261
4262
4263
4264
4265
4266
4267
4268
4269
4270
4271
4272
4273
4274
4275
4276
4277
4278
4279
4280
4281
4282
4283
4284
4285
4286
4287
4288
4289
4290
4291
4292
4293
4294
4295
4296
4297
4298
4299
4300
4301
4302
4303
4304
4305
4306
4307
4308
4309
4310
4311
4312
4313
4314
4315
4316
4317
4318
4319
4320
4321
4322
4323
4324
4325
4326
4327
4328
4329
4330
4331
4332
4333
4334
4335
4336
4337
4338
4339
4340
4341
4342
4343
4344
4345
4346
4347
4348
4349
4350
4351
4352
4353
4354
4355
4356
4357
4358
4359
4360
4361
4362
4363
4364
4365
4366
4367
4368
4369
4370
4371
4372
4373
4374
4375
4376
4377
4378
4379
4380
4381
4382
4383
4384
4385
4386
4387
4388
4389
4390
4391
4392
4393
4394
4395
4396
4397
4398
4399
4400
4401
4402
4403
4404
4405
4406
4407
4408
4409
4410
4411
4412
4413
4414
4415
4416
4417
4418
4419
4420
4421
4422
4423
4424
4425
4426
4427
4428
4429
4430
4431
4432
4433
4434
4435
4436
4437
4438
4439
4440
4441
4442
4443
4444
4445
4446
4447
4448
4449
4450
4451
4452
4453
4454
4455
4456
4457
4458
4459
4460
4461
4462
4463
4464
4465
4466
4467
4468
4469
4470
4471
4472
4473
4474
4475
4476
4477
4478
4479
4480
4481
4482
4483
4484
4485
4486
4487
4488
4489
4490
4491
4492
4493
4494
4495
4496
4497
4498
4499
4500
4501
4502
4503
4504
4505
4506
4507
4508
4509
4510
4511
4512
4513
4514
4515
4516
4517
4518
4519
4520
4521
4522
4523
4524
4525
4526
4527
4528
4529
4530
4531
4532
4533
4534
4535
4536
4537
4538
4539
4540
4541
4542
4543
4544
4545
4546
4547
4548
4549
4550
4551
4552
4553
4554
4555
4556
4557
4558
4559
4560
4561
4562
4563
4564
4565
4566
4567
4568
4569
4570
4571
4572
4573
4574
4575
4576
4577
4578
4579
4580
4581
4582
4583
4584
4585
4586
4587
4588
4589
4590
4591
4592
4593
4594
4595
4596
4597
4598
4599
4600
4601
4602
4603
4604
4605
4606
4607
4608
4609
4610
4611
4612
4613
4614
4615
4616
4617
4618
4619
4620
4621
4622
4623
4624
4625
4626
4627
4628
4629
4630
4631
4632
4633
4634
4635
4636
4637
4638
4639
4640
4641
4642
4643
4644
4645
4646
4647
4648
4649
4650
4651
4652
4653
4654
4655
4656
4657
4658
4659
4660
4661
4662
4663
4664
4665
4666
4667
4668
4669
4670
4671
4672
4673
4674
4675
4676
4677
4678
4679
4680
4681
4682
4683
4684
4685
4686
4687
4688
4689
4690
4691
4692
4693
4694
4695
4696
4697
4698
4699
4700
4701
4702
4703
4704
4705
4706
4707
4708
4709
4710
4711
4712
4713
4714
4715
4716
4717
4718
4719
4720
4721
4722
4723
4724
4725
4726
4727
4728
4729
4730
4731
4732
4733
4734
4735
4736
4737
4738
4739
4740
4741
4742
4743
4744
4745
4746
4747
4748
4749
4750
4751
4752
4753
4754
4755
4756
4757
4758
4759
4760
4761
4762
4763
4764
4765
4766
4767
4768
4769
4770
4771
4772
4773
4774
4775
4776
4777
4778
4779
4780
4781
4782
4783
4784
4785
4786
4787
4788
4789
4790
4791
4792
4793
4794
4795
4796
4797
4798
4799
4800
4801
4802
4803
4804
4805
4806
4807
4808
4809
4810
4811
4812
4813
4814
4815
4816
4817
4818
4819
4820
4821
4822
4823
4824
4825
4826
4827
4828
4829
4830
4831
4832
4833
4834
4835
4836
4837
4838
4839
4840
4841
4842
4843
4844
4845
4846
4847
4848
4849
4850
4851
4852
4853
4854
4855
4856
4857
4858
4859
4860
4861
4862
4863
4864
4865
4866
4867
4868
4869
4870
4871
4872
4873
4874
4875
4876
4877
4878
4879
4880
4881
4882
4883
4884
4885
4886
4887
4888
4889
4890
4891
4892
4893
4894
4895
4896
4897
4898
4899
4900
4901
4902
4903
4904
4905
4906
4907
4908
4909
4910
4911
4912
4913
4914
4915
4916
4917
4918
4919
4920
4921
4922
4923
4924
4925
4926
4927
4928
4929
4930
4931
4932
4933
4934
4935
4936
4937
4938
4939
4940
4941
4942
4943
4944
4945
4946
4947
4948
4949
4950
4951
4952
4953
4954
4955
4956
4957
4958
4959
4960
4961
4962
4963
4964
4965
4966
4967
4968
4969
4970
4971
4972
4973
4974
4975
4976
4977
4978
4979
4980
4981
4982
4983
4984
4985
4986
4987
4988
4989
4990
4991
4992
4993
4994
4995
4996
4997
4998
4999
5000

TABLE 15

```

sort-nodes(node)

  Let nodes = {}
  For child in node.children
    nodes = append(nodes, sort-nodes(child))
  nodes += node
  return(nodes)

compute-inner-values(sorted-nodes, node-value-function)

For node in sorted-nodes
  If (node.type = terminal)
    node.inner-value = apply(node-value-function, node.terminal-object)
  Else If (node.type = OR)
    node.inner-value = infinity
    For child in node.children
      If (child.inner-value < node.inner-value)
        node.inner-value = child.inner-value
        node.best-child = child
  Else If (node.type = AND)
    node.inner-value = 0
    For child in node.children
      node.inner-value += child.inner-value

find-optimal-solution(root-node, node-value-function)

Subroutine get-node-solution(node)

  If (node.type = terminal)
    return(list(node.terminal-object))
  Else If (node.type = OR)
    return(get-node-solution(node.best-child))
  Else If (node.type = AND)
    Let solution = {}
    For child in node.children
      solution = append(solution, get-node-solution(child))
    return(solution)

compute-inner-values(sort-nodes(root-node), node-value-function)
return(get-node-solution(root-node))

```

FINDING MINIMUM VALUE

Another procedure 304b finds, for each node, the best (i.e., minimum) value of some value-function over all the set of pricing solutions involving that node. Price function 306a finds for
5 each itinerary, the cheapest price of any pricing solution that contains that itinerary. These values can be computed efficiently, if the value-function can be decomposed into a node-value-function.

Sub 23
~~The best price value function 306a computes inner values, as
10 above, and computes for every node, an outer-value, equal to the minimum value contributed by all parts of the graph except that represented by the node. For each node, the minimum value of the value-function over all solutions that involve the node, (i.e., the total-value) is computed as the sum of that node's inner-value and outer value.~~
15

The outer-value and total-value of a node are computed in a manner very similar to the computation of the inner-value. In particular, the outer-value for each node is calculated starting from the root of the graph, that has an outer-value of 0. Each
20 node propagates outer-values down to its children. An OR-node passes its outer-value unchanged. An AND-node adds to its outer-value the inner-values of all children except that being propagated to. At every node, after the outer-value has been computed, the total-value is computed as the sum of the inner-value and outer-value.
25

When outer-values are propagated from a node to its children, a minimum computation is performed. This is because each child may have more than one parent, and its outer-value must be the minimum outer-value contributed by any parent. See
30 TABLE 16 below.

TABLE 16

```

compute-outer-and-total-values(root-node, node-value-function)
    // Sort nodes and computer inner-values.
    Let sorted-nodes = sort-nodes(root-node)
    compute-inner-values(sorted-nodes, node-value-function)

    Let reversed-nodes = reverse(sorted-nodes)

// Initialize all nodes to have outer-values of infinity.
For node in reversed-nodes
    node.outer-value = infinity

// The root-node has an outer-value of 0.
first(reversed-nodes).outer-value = 0

For node in reversed-nodes

    // Compute the total-value for the node.
    node.total-value = node.inner-value + node.outer-value

    If (node.type = OR)
        // For OR nodes, the outer-value is propagated down to its children unchanged.
        For child in node.children
            child.outer-value = minimum(child.outer-value, node.outer-value)
    Else If (node.type = AND)
        // For AND nodes, the outer-value is propagated down by adding the inner-values of
        // all but the child being propagated to. This is equal to the node=s inner-value minus
        // the child=s inner-value, which is equal to the node=s total-value minus the child=s
        // inner-value.
        For child in node.children
            child.outer-value = minimum(child.outer-value, node.total-value - child.inner-value)

```

INVALIDATING NODES

~~It may be desirable to "invalidate" 304e certain nodes from the pricing-graph 38'. For example, itineraries containing or not containing specified airlines could be marked as not participating in the above algorithms, enabling the algorithms to find the best solutions involving or not involving these itineraries. The above algorithms can be easily adapted to accommodate checking whether the node is valid. In particular, the computation of inner-values, the first step in all the above~~

algorithms, is modified to mark for every node whether the node
 represents any valid partial pricing-solutions given a specific
 query parameter. This information can be used in the rest of the
 algorithms. Every terminal node contains a field "valid?" that
 is either true or false. The compute-inner-values procedure uses
 these values to set the "valid?" field for non-terminals. See
 TABLE 17 below.

TABLE 17

```

// Initialize all nodes to have outer-values of infinity.
For node in reversed-nodes
  node.outer-value = infinity

// The root-node has an outer-value of 0.
first(reversed-nodes).outer-value = 0

For node in reversed-nodes
  If (node.valid? = true)

    // Compute the total-value for the node.
    node.total-value = node.inner-value + node.outer-value

    If (node.type = OR)
      // For OR nodes, the outer-value is propagated down to its children unchanged.
      For child in node.children
        child.outer-value = minimum(child.outer-value, node.outer-value)
    Else If (node.type = AND)
      // For AND nodes, the outer-value is propagated down by adding the inner-values of
      // all but the child being propagated to. This is equal to the node=s inner-value minus
      // the child=s inner-value, which is equal to the node=s total-value minus the child=s
      // inner-value.
      For child in node.children
        child.outer-value = minimum(child.outer-value,
                                     node.total-value - child.inner-value)
  
```

```

sort-nodes (node)
If (not(find(node,nodes)))
For child in node.children
sort-nodes-inner(child)
nodes +=node
sort-nodes-inner(node);
return (nodes)
compute-inner-values(sorted-nodes, node-value-function)

```

```

For node in sorted-nodes
  If (node.type = terminal)
    node.inner-value = apply(node-value-function, node.terminal-object)
  Else If (node.type = OR)
    node.inner-value = infinity
    node.valid? = false
    For child in node.children
      If (child.valid? = true and child.inner-value < node.inner-value)
        node.inner-value = child.inner-value
        node.best-child = child
        node.valid? = true
  Else If (node.type = AND)
    node.inner-value = 0
    node.valid? = true
    For child in node.children
      If (child.valid? = true)
        node.inner-value += child.inner-value
  Else
    node.valid? = false

```

```

find-optimal-solution(root-node, node-value-function)

```

```

Subroutine get-node-solution(node)

  If (node.type = terminal)
    return(list(node.terminal-object))
  Else If (node.type = OR)
    return(get-node-solution(node.best-child))
  Else If (node.type = AND)
    Let solution = {}
    For child in node.children
      solution = append(solution, get-node-solution(child))
    return(solution)

```

```

compute-inner-values(sort-nodes(root-node), node-value-function)
If (root-node.valid? = true)
  return(get-node-solution(root-node))
Else
  return(nil)

```

```

compute-outer-and-total-values(root-node, node-value-function)

```

```

// Sort nodes and computer inner-values.
Let sorted-nodes = sort-nodes(root-node)
compute-inner-values(sorted-nodes, node-value-function)

Let reversed-nodes = reverse(sorted-nodes)

```

```

// Initialize all nodes to have outer-values of infinity.
For node in reversed-nodes
    node.outer-value = infinity

// The root-node has an outer-value of 0.
first(reversed-nodes).outer-value = 0

For node in reversed-nodes
    If (node.valid? = true)

        // Compute the total-value for the node.
        node.total-value = node.inner-value + node.outer-value

        If (node.type = OR)
            // For OR nodes, the outer-value is propagated down to its children unchanged.
            For child in node.children
                child.outer-value = minimum(child.outer-value, node.outer-value)
        Else If (node.type = AND)
            // For AND nodes, the outer-value is propagated down by adding the inner-values of
            // all but the child being propagated to. This is equal to the node=s inner-value minus
            // the child=s inner-value, which is equal to the node=s total-value minus the child=s
            // inner-value.
            For child in node.children
                child.outer-value = minimum(child.outer-value,
                                            node.total-value - child.inner-value)

```

ENUMERATING PRICING SOLUTIONS

It is often desirable to arbitrarily enumerate many pricing solutions: the best, the second-best, the third-best, etc.

The enumeration algorithm 304c maintains a queue of partial-solutions, ordered by the lowest possible total value of the value-function over all complete solutions that contain the partial-solution. At the start of the search, a single partial solution is constructed from the root node of the pricing-graph 38'. At each step the best partial-solution is dequeued, and expanded. Each partial-solution has a set of non-terminal nodes and a set of terminal objects. A partial-solution is expanded by selecting a non-terminal node and substituting the node's children (all of its children in the case of an AND, one of its children in the case of an OR). If a dequeued partial-solution contains only terminal objects, it is complete, and is returned. This process continues until the desired number of pricing-

solutions that can be specified by a user has been produced.

The algorithm can accommodate value-functions that cannot be decomposed into the sum of a node-value-function. It does this by applying a second penalty-value-function to partial pricing-solutions as it constructs them. This function returns a non-negative number when given a new terminal object and existing set of terminal objects. The number is added to the values produced by the normal node-value-function. If the number is positive, it acts as a penalty. An example of how this could be used is for the case where a penalty is applied if travel in two slices is on different airlines. The penalty-value-function would return a (positive) penalty if the terminal was an itinerary, and the set of existing terminals contained an itinerary with travel on different airlines. Otherwise it would return 0. See TABLE 18 below.

TABLE 18

```
compute-inner-values(sorted-nodes, node-value-function)
  For node in sorted-nodes
    If (node.type = terminal)
      node.inner-value = apply(node-value-function, node.terminal-object)
    Else If (node.type = OR)
      node.inner-value = infinity
      node.valid? = false
      For child in node.children
        If (child.valid? = true and child.inner-value < node.inner-value)
          node.inner-value = child.inner-value
          node.best-child = child
          node.valid? = true
```

```

Else If (node.type = AND)
  node.inner-value = 0
  node.valid? = true
  For child in node.children
    If (child.valid? = true)
      node.inner-value += child.inner-value
  Else
    node.valid? = false

```

find-optimal-solution(root-node, node-value-function)

Subroutine get-node-solution(node)

```

If (node.type = terminal)
  return(list(node.terminal-object))
Else If (node.type = OR)
  return(get-node-solution(node.best-daughter))
Else If (node.type = AND)
  Let solution = {}
  For child in node.children
    solution = append(solution, get-node-solution(child))
  return(solution)

```

compute-inner-values(sort-nodes(root-node), node-value-function)

```

If (root-node.valid? = true)
  return(get-node-solution(root-node))
Else
  return(nil)

```

compute-outer-and-total-values(root-node, node-value-function)

```

// Sort nodes and computer inner-values.
Let sorted-nodes = sort-nodes(root-node)
compute-inner-values(sorted-nodes, node-value-function)

```

Let reversed-nodes = reverse(sorted-nodes)

```

// Initialize all nodes to have outer-values of infinity.
For node in reversed-nodes
  node.outer-value = infinity

```

```

// The root-node has an outer-value of 0.
first(reversed-nodes).outer-value = 0

```

```

For node in reversed-nodes
  If (node.valid? = true)

```

```

// Compute the total-value for the node.
node.total-value = node.inner-value + node.outer-value

If (node.type = OR)
    // For OR nodes, the outer-value is propagated down to its children unchanged.
    For child in node.children
        child.outer-value = minimum(child.outer-value, node.outer-value)
Else If (node.type = AND)
    // For AND nodes, the outer-value is propagated down by adding the inner-values of
    // all but the child being propagated to. This is equal to the node=s inner-value minus
    // the child=s inner-value, which is equal to the node=s total-value minus the child=s
    // inner-value.
    For child in node.children
        child.outer-value = minimum(child.outer-value,
                                    node.total-value - child.inner-value)

```

Referring to FIG. 8, a diversity process 350 for selecting a diverse set of travel options from a larger set of candidate travel options is shown. The diversity process includes generating 352 an ordered list of travel requirements that represent conditions possibly required for a travel option to be the best travel option to generate. The diversity process 350 selects 354 for each travel requirement the one or more travel options that satisfy the requirement preferably by choosing those travel options that best satisfy one or more travel preference functions that can be used to order travel options.

For example, the air travel planning system generates the following 10 travel requirements for a set of travel options that each include one or more flights.

1. <none>
2. all flights on American Airlines.
3. all flights on United Airlines.
4. non-stop.
5. departing in morning.
6. departing in evening.

7. non-stop on American Airlines.
8. non-stop on United Airlines.
9. non-stop in morning.
10. non-stop in evening.

5 The diversity process 350 for each of the requirements the
planning system selects 354 from the large set of candidate
travel options e.g., the cheapest travel option that satisfies
the requirement. The cheapest option is generated; the cheapest
options all on American Airlines; the cheapest travel options all
10 on United Airlines; the cheapest travel options that are
non-stop; and so forth. These travel options are displayed 356
to provide a traveller a desirable option even if the traveller
has restrictions on the times the traveller can travel, or
preferences for one airline over another. These options are
15 possible more desirable than if the system had merely generated
and sent the 10 cheapest solutions without regard to producing a
diverse set of solutions taking into consideration preferences of
the traveller.

20 Referring to FIG. 9, an example 360 of a diversity process
350 is shown. The diversity process 360 generates a diverse list
of travel options from a larger set of travel options. The
diversity process iterates through a set of travel requirements
and selects the best travel option for each requirement. The
diversity process 360 can include an optional process that may
25 improve efficiency in some cases by eliminating more-restrictive
travel requirements that are satisfied by solutions selected for
less-restrictive travel requirements.

30 For example, given the ordered travel requirements in the
list above, if the cheapest travel option selected for the travel
requirement "all flights on American Airlines" happens to be a
non-stop option, then the travel requirement "non-stop on

American Airlines" is removed from the list of travel requirements to be satisfied, since the same travel option selected for the first requirement will be the best for the second more-specific requirement. This is only applied if the all restrictions in the first requirement are also found in the second requirement.

10 ~~The diversity process 360 thus includes a procedure for generating a diverse list of (N) travel options (Rts) from a larger list of travel options (Ts), that are the best travel options for a set of travel requirements (R), as defined by an ordering function F. The diversity process 360 generates 362 an prioritized (ordered) list of requirements Rs, and sorts 364 the list of travel options (Ts) by function (F) to produce a best-first ordered list (Ts2). The diversity process 360, initializes the list of result travel options (RTs) to be empty. If the remaining list of requirements (Rs) is empty, the process 360 returns an ordered list of diverse travel options (Rts). Otherwise, the diversity process selects 366 the first travel requirement (R) from the ordered list of requirements (Rs) and removes 368 a requirement (R) from the requirement list (Rs). The diversity process 360 find 370 a first (e.g., best) option T in the best-first ordered list (Ts2) that satisfies travel requirement (R).~~

25 ~~If the set of travel options is represented by a data structure that stores a large set of travel options by representing permitted combinations of smaller travel option components such as airline flights and fares. In such cases the travel option selection process above is implemented using a more complicated operation than searching through an ordered list. With the pricing-graph the process for finding 370 the best travel option that satisfies a travel requirement is implemented for a representation that expresses travel options in terms of,~~

A24
Cont'd

~~permitted combinations of smaller travel option components by
disabling option components inconsistent with the requirement.~~

As shown in FIG. 9A, the process 360 can use the node
invalidating functions to invalidate nodes 422 in the pricing
graph 38 that are inconsistent with the requirements. The
process 360 applies 424 an enumeration algorithm that extracts the
best solution from the pricing graph representation. The
diversity process 360 calls an enumeration function, as described
above, to enumerate all of the valid pricing solutions from the
pricing graph that are remaining after the diversity process
selectively invalidated nodes in the graph inconsistent with the
travel requirements.

Sub A25

If no option in the best-first ordered list (Ts2) satisfies
72 the requirement (R), the process 360 goes to check 374 if the
remaining list of requirements (Rs) is empty. Otherwise, the
diversity process determines 376 if a travel option T is not
already in result travel options list (Rts). If the option T is
not in the list (Rts), the diversity process adds 378 the travel
option T to end of the result travel option list (Rts). If the
size of the travel option list (RTs) is equal to or greater than
N 380 the process returns the ordered list of diverse travel
options.

Sub A29

Referring to FIG. 10A, the diversity process 360 could
optionally determine 382 for a travel requirement (R2) in the set
of travel requirements (Rs), whether the requirement (R2) is
included in a prior requirement (R), and whether the travel
option T also satisfies 384 the requirement (R2). If the travel
option T satisfies the requirement (R2), the process 360 can
remove 386 the requirement R2 from the requirement list (Rs) and
return to determine 74 (FIG. 3) if the remaining list of
requirements is empty.

Referring to FIG. 11, the process 362 to generate a

prioritized list of travel requirements is shown. The list may be a fixed list, for example the list of ten requirements in the example above. Alternatively, the list may be generated taking into account the number of solutions required, the ordering function, and the large set of candidate travel options. For example, the list may be generated 362 by filling 392 in a set of template requirements. A sample set of templates for air travel is

1. no requirement.
2. all flights on <airline>
3. non-stop.
4. outbound departure in <morning or afternoon or evening>.
5. return departure in <morning or afternoon or evening>.
6. outbound departure date <date>.
7. return departure date <date>.
8. non-stop on <airline>.
9. outbound departure date <date1> and return departure date <date2>.

~~The large candidate set of travel options may be analyzed 394 to find all parameters e.g., airlines found in any travel option, all departure dates for outbound and return, and all departure parts-of-day (morning, afternoon, evening) for outbound and return. The ordered list of requirements is generated by filling 96 in for each template all airlines, dates and parts-of-day present in the options.~~

The diversity process 360 can be run more than once with different travel option preference functions (a set of F's). For example, a travel planning system may output a diversity of travel options that include diverse options that are cheap and diverse options that are convenient, reflecting uncertainty in whether a traveller is cost-sensitive or convenience-sensitive.

Referring to FIG. 12, an alternative diversity process 100 to generate a diverse set of travel options from a larger set of travel options is shown. The alternative diversity process 400 generates the best one or more travel options as defined by each of a set of different travel preference functions. The alternative diversity process 400 defines a set of travel preference functions with each function capable to order travel options. In one example, the set might include "cheapest", "quickest", and "most-convenient" where each is a function that assigns a numerical score to a complete travel option (such as price, total-trip-time, and total trip-time with penalties for stops). Functions that assign numerical values based on combinations of cost and convenience are possible, such as ~~functions that weigh both price and time.~~

~~Given set of travel options Ts 401, a set of preference functions Fs, and a desired number of answers for each preference function Ns, the alternative diversity process 400 returns a reduced set of diverse travel options Rts. The alternative diversity process initializes 402 a list of result travel options RTs to be empty and for each preference function F in the set of preference functions Fs and number of travel options (N) in the set of desired number of answers in each preference function (Ns), the alternative diversity process 400 computes 404 the N best travel options in Ts as defined by F. For each travel option T, unless the travel option T is in the set of diverse travel options Rts 406, the alternative diversity process 400 adds 408 the travel option T to the set of diverse travel options Rts checks 410 the number of options. The alternative diversity process 400 outputs 412 the diverse set of travel options (RTs).~~

~~The diversity process can be run more than once with different travel option preference functions (a set of F's). For example, a travel planning system may wish to output a diversity~~

#33
Cont'd

~~of travel options that include diverse options that are cheap and~~
~~deverse options that are convenient, reflecting uncertainty in~~
~~whether a traveller is cost sensitive or convenience sensitive.~~

5 A computer travel planning system that outputs a
diversity of travel options may be built by combining a travel
planning system that transmits a larger set of solutions to a
second computer system that reduces the set of travel options
using diversity procedures as described above.

Other Embodiments

10 It is to be understood that while the invention has been
described in conjunction with the detailed description thereof,
the foregoing description is intended to illustrate and not limit
the scope of the invention, which is defined by the scope of the
appended claims. Other aspects, advantages, and modifications
are within the scope of the following claims.

What is claimed is: